



पूर्वोत्तर इंदिरा गांधी क्षेत्रीय स्वास्थ्य एवं आयुर्विज्ञान संस्थान, शिलांग
NORTH EASTERN INDIRA GANDHI REGIONAL INSTITUTE OF HEALTH & MEDICAL SCIENCES, SHILLONG
(भारत सरकार, स्वास्थ्य एवं परिवार कल्याण मंत्रालय, स्वायत्त संस्थान)
(An Autonomous Institute, Ministry of Health and Family Welfare, Government of India)
निदेशक ब्लॉक, मावडीयांगडीयांग, शिलांग - 793018 मेघालय
Director's Block, Mawdiangdiang, Shillong - 793018 Meghalaya

E-mail - info.neigrihms@gov.in
www.neigrihms.gov.in
EPABX : (0364) 2538025

No NEIGR/ENGG/91/2023

Dated:- 3rd October, 2023

NOTICE INVITING QUOTATION

On behalf of the Institute, Sealed quotations for **Repair and Painting work in Faculty Block** are invited from registered contractors for the following work upto **10th October, 2023** by **2:00 P M** and the same will be opened on the same date and time as per details below:

Sl No	Name of work	Estimated cost	Earnest Money Deposit (EMD)
1	Repairing and Painting work in Faculty Block	Rs. 1,53,354/-	Rs. 3070/-

Terms and conditions:

1. NEIGRIHMS reserves the right to accept or reject any or all quotation without assigning any reason thereof.
2. If the contractor fails to complete the execution and completion of the works as specified in the letter of award and if extension of time is not granted, if any, the contractor shall be bound to pay a liquidated damages a sum of 0.5% (percent) per week of delay for such default subject to a maximum of 5% of the contract price.
3. The quotation should be submitted in a sealed cover and superscripted with the name of work addressed to the Executive Engineer (Civil), NEIGRIHMS
4. The rate should be inclusive of all taxes and duties.
5. Performance Security @ 5% if applicable will have to be submitted by the lowest quotationer.
6. The rates shall be applicable for a period of 1(one) year from date of award or till finalization of new rate whichever is earlier.
7. All bidders are required to quote their GSTIN number.

Interested bidders may submit their quotations as per the price bid format at Annexure - I at the Office of the Undersigned upto **1400 hrs on 10th October ,2023**

Executive Engineer (C)

Copy to: 1. Notice Board
2. Office file

Name of the Work: - Repair and Painting work in Faculty Block

Sl No	Description	Unit	Quantity	Rate	Amount
1	Dismantling old plaster or skirting raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50 metres lead.	Sqm	6.95		
2	12 mm cement plaster of mix: a) 1:4 (1 cement: 4 fine sand)	Sqm	6.95		
3	Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS:15622 (thickness to be specified by the manufacturer), of approved make, in all colours and shades of any size as approved by Engineer-in-Charge, in walls, skirting, risers of steps and dados, over 12 mm thick bed of cement mortar 1:3 (1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm, including pointing in white cement mixed with pigment of matching shade complete (a) Normal range	Sqm	6.95		
4	Surface preparation a) Removing existing white or colour wash on wall surfaces by steel wire brushing and/ or scraping, sand papering and preparing the surface smooth including necessary repairs to scratches complete	Sqm	184.78		
5	Providing and applying Plaster of Paris putty of 2 mm thickness over plastered surface to prepare the surface even and smooth complete.	Sqm	92.39		
6	Wall painting with plastic emulsion paint of approved brand and manufacture to give an even shade: Old work (one or more coats)	Sqm	1506.6		
7	Providing and fixing of frame work made of special sections, power pressed from M.S. sheets and galvanized with zinc coating of 120 gms/sqm (both side inclusive) as per IS:277 and consisting of angle cleats of size 25 mm wide x 1.6 mm thick with flanges of 27 mm and 37 mm, at 1200 mm centre to centre, one flange fixed to the ceiling with dash fastener 12.5 mm dia. x 50mm long with 6 mm dia. bolts, other flange of cleat fixed to the angle hangers of 25x10x0.50 mm of required length with nuts & bolts of required size etc.etc (b) 12.5 mm thick tapered edge gypsum moisture resistant board	Sqm	8.28		
8	Providing and fixing P.V.C. low level flushing cistern with manually controlled device (handle lever) conforming to IS:7231, with all fittings and fixtures complete (a) 10 litre capacity - White	Each	1		
9	Providing and fixing solid plastic seat with lid for pedestal type W.C. pan complete (c) Coloured (other than black & white) solid plastic seat with lid	Each	1		
10	Providing and laying Polished Granite stone flooring in required design and patterns, in linear as well as curvilinear portions of the building all complete as per the architectural drawings with 18 mm thick stone slab over 20 mm (average) thick base of cement mortar 1:4 (1 cement: 4 coarse sand) laid and jointed with cement slurry and pointing with white cement slurry admixed with pigment of matching shade including rubbing, curing and polishing, etc. all complete as specified and as directed by the Engineer-in-Charge.	Sqm	1		

Signature of Contractor